



CMB

Thermoplastic LED Exit Sign and Emergency Combo

DATE:

COMMENTS:

PROJECT

FEATURES

- Two fully-adjustable watt lamp heads
- Universal mounting canopy included for ceiling mounting: universal, single, or double face
- Snap together, quick-fit installation with field selectable chevron directional indicators
- Long life, high intensity LED array available in red or green
- Damp location standard
- Maintenance free, 6V nickel cadmium batteries provide 90 minutes of run time
- Up to 3W remote capability optional to power optional remote heads (two heads maximum)
- Meets CSA C22.2 No. 141-02
- UL Listed



ORDERING INFORMATION *CMB-EM-R-U-WH-MTEBP-L1*

1. SERIES	2. OPERATION	3. LETTER COLOR	4. FACE COUNT	5. HOUSING COLOR	6. MOUNTING
CMB	EM		U		MTEBP
	EM Ni-Cad Battery Backup	R Red G Green	U Universal	BK Black WH White	MTEBP Universal Mount

7. LAMP SOURCE

L1 LED 1W
NH No Heads

8. OPTIONS

BLANK = NO OPTION
SD Self-Diagnostics
EB Remote Capacity¹
HO High-Output Lamps

ORDERING NOTES

1. If using the remote capacity option without any remote lamp heads attached, the base unit run time is extended to greater than 2 hours

ACCESSORIES; ORDER SEPARATELY

- WG 7** = Wire guard 28.0" X 21.0" X 10.0"

SPECIFICATIONS

ELECTRONICS

- Electronic Control Circuit and Isolation Transformer provide current control and circuit protection, ensuring optimum LED efficiency and life
- 120/277 VAC field-selectable inputs
- Solid state transfer relay for reliability

CONSTRUCTION

- Injection molded VO flame retardant, high impact thermoplastic housing

LETTERS

- 6" high; 0.75" stroke

APPROVALS

- UL 924
- NFPA Life Safety Code 101
- NFPA 70- NEC
- OSHA

TEMPERATURE RATING

- From 32°F to 104°F

WARRANTY

- Isolite offers a 5-year limited warranty. For further details, refer to General Warranty and Obligations in the Isolite manual or on our website. Lamps not warranted

DIMENSIONS

