

DATE: [REDACTED]	COMMENTS: [REDACTED]
PROJECT [REDACTED]	

FEATURES

- New York City Approved 8" letters with 1" stroke
- Ultra-bright, energy efficient, long-life Red LEDs
- Internal solid-state transfer switch automatically connects the internal battery to LED board and LED lamp heads for minimum 90-minute emergency illumination
- Fully automatic solid-state, two-rate charger initiates battery charging to recharge a discharged battery in 24 hours
- 4.8V long-life, maintenance-free, rechargeable Ni-Cad battery
- Charge rate/power "ON" LED indicator light and push-to-test switch for mandated code compliance testing
- 120/277 VAC field-selectable inputs (with the exception of the C1/C2 (dual circuit) option which requires voltage specification upon ordering)



ORDERING INFORMATION *EXAMPLE: EDC-NYC-AC-R-1-BA-BA-MTEBP*

1. SERIES	2. OPERATION	3. ILLUMINATION	4. FACE COUNT	5. FACE COLOR
EDC-NYC	-	R	-	-
	AC AC Only EM Ni-Cad Battery Backup	R Red	1 Single 2 Double U Universal	BA Brushed Aluminum BK Black WH White
6. FRAME COLOR	7. MOUNTING	8. OPTIONS		
	MTEBP	BLANK = NO OPTION		
BA Brushed Aluminum BK Black WH White	MTEBP Universal Mount	CX Dual Circuit (120/277 VAC) (AC Only) SD Self-Diagnostics (EM Only) TP Tamperproof Screws		



ARROWS

- Field selectable knockout chevron directional indicators

CONSTRUCTION

- Premium-grade, aluminum housing. Also available in black or white powder-coat finishes

WEIGHT

- • 5 lb

TEMPERATURE RATING

- From 32°F to 122°F

APPROVALS

- New York City Approved
- UL 924
- NFPA Life Safety Code 101
- NFPA 70-NEC
- OSHA

WARRANTY

- Isolite offers a 3-year limited warranty. For further details, refer to General Warranty and Obligations in the Isolite manual or on our website. Lamps not warranted

DIMENSIONS

