

ELF

Flush Mounted Architectural Emergency Light

| DATE: | COMMENTS: |
|---------|-----------|
| | |
| PROJECT | |
| | |
| | |

FEATURES

- Four Integrated 1W LED heads product bright light that will not fade over time.
- Flush mounted design makes the emergency lights blend into the ceiling.
- Adjustable LEDs allow for up to 50ft light spacing.
- Available with push-to-test and self-diagnostic versions.
- Meets all NFPA 101 life safety requirements for run time and recharge time.
- Available in textured white and textured black finishes.
- ELF lights ship with trim rings for both oval and rectangular aesthetics.
- Recessed mounting includes bar hangers and is compatible with drop ceiling or plaster-board installations.



CLICK THE IMAGE TO VIEW ALTERNATE PRODUCT PHOTOS

Only available with Adobe Acrobat and Acrobat Reader

ORDERING INFORMATION *ELF-4W-WH-MRC-SD*

| 1. SERIES | 2. OPERATION | 3. HOUSING COLOR | 4. MOUNTING | 5. OPTIONS |
|-----------|--------------|------------------|----------------------------|---------------------------------------|
| ELF | - 4W | - WH | - MRC | - |
| | 4W 4 Watts | WH White | MRC Recessed Ceiling Mount | BLANK = NO OPTION SD Self-Diagnostics |

SPECIFICATIONS

CONSTRUCTION

- Recessed mount includes hanger bars.
- Compatible with drop ceiling mount installations.
- Injection-molded, engineering grade, 5VA flame-retardant, impact resistant, thermoplastic housing in white or black finish
- Thermoplastic Oval and Rectangle trim plates in white or black finish included.

ELECTRICAL

- Input Voltage: 120/277 Field Selectable
- Battery Type: 4.8V NiMH
- Light Source: 4x 1W Integrated, Adjustable LEDs

TEMPERATURE RATING

32°F to 122°F (0°C to 50°C)

APPROVALS

- UL 924
- NFPA 101 Life Safety Code
- NFPA 70-NEC
- OSHA

WARRANTY

Isolite offers a 5-year limited warranty. For further details, refer to General Warranty and Obligations in the Isolite manual or on our website. Lamps not warranted.







DIMENSIONS











