



| | |
|----------|------|
| Project | |
| Notes | |
| Type | Date |
| Cat. No. | |

EXS™ Series **Edge Lit LED Exit Sign**



APPLICATIONS

The EXS series is an surface mount edge lit LED exit sign that features an architectural, slim design to fit into any environment offering specification grade aesthetics with in field installation flexibility. Attractive and functional, the EXS series is completely self-contained and utilizes reliable, energy efficient LED illumination. EXS series edge-lit exits are well suited for any application requiring attractive edge-lit exit sign. Typical installations include commercial spaces such as retail, offices or medical facilities but can be applied in any space where an upgrade appearance is desired.

- EXS Series**
- EXS-1-A-G
 - EXS-1-A-R
 - EXS-2-A-G
 - EXS-2-A-R



Specification Features

Construction

Premium-grade, extruded aluminum housing (also available in optional black or white powder-coated finishes.). Self-adhesive Chevron appliques and guide template provided for directional indication.

Qualifications

Meets UL924, NFPA 11 life safety Code, NEC, OSHA Local and State Codes. UL listed for damp locations (0° C - 50° C).

Warranty

5-year Limited Warranty on all electronics and housing. Battery pro rated for 5 years.

Electrical

Dual 120/277 voltage. Charge rate/power "ON" LED indicator light and push-to-test switch for mandated code compliance testing. 4.8V long-life, maintenance - free, rechargeable NiCad. Internal solid-state transfer switch automatically connects the internal battery to the LED lamp head for minimum 90-minute emergency illumination. Fully automatic solid-state, two-rate charger initiates battery charging to recharge a discharged battery in 24 hours.

Installation

Aluminium mounting canopy included for top, end, or back mount.

Limited Warranty 5-years

Quick Ship

- EXS-1-A-R
- EXS-2-A-R

Ordering Information

Example: EXS-1-A-G-AC

| EXS | 1 | A | R | AC | | |
|---|------------------------|-------------------------------------|--|---|--|--|
| Series EXS Edge Lit LED Exit Sign | Faces 1 2 | Housing Color A- aluminum | Lettering R - Red G - Green | Battery Blank- 90 minute battery backup AC- AC only | | |

Specifications and Dimensions subject to change without notice.

Performance Summary

| | |
|-----------------|----------------------------|
| Input Voltage | 120V/277V |
| Input Frequency | 50/60 Hz |
| Rated Wattage | 3W |
| Operating Temp. | -18°C to 40°C |
| Rated Life | 60,000 hours |
| L70 | > 72,000 hours or > 45,000 |
| Power Factor | > 0.9 |

Performance Data

| Lens Type | Form Factor | Catalog No. | Rated Wattage (W) |
|-----------|-------------|-------------|-------------------|
| None | | EXS-1-A-G | 3 |
| | | | |
| | | EXS-2-A-G | 3 |
| | | | |

NOTES:

- ¹ Made to order items. Minimum 90 day lead time. Minimum 500 order quantity.
- ² Energy star listed
- ⁴ Typical color consistency. May vary or be changed.
- ⁵ L70 hours calculated based on LED package manufacturer LM80 report and ISTMT report of LED in luminaire. Stated values are for select catalog numbers. Contact manufacturer for detailed information
- ⁶ Actual performance may differ as a result of end-user environment and application. All values are design or typical values, measured under laboratory conditions at 25 °C.



Specifications and Dimensions subject to change without notice.

Product Dimensions

EXS

