



Project	
Notes	
Type	Date
Cat. No.	

**LSMP™ Series** LED Surface Mounted Puff



**DESCRIPTION**

The LSMP Series of LED Puff fixtures are cost effective and are an energy-saving replacement for less efficient fluorescent puff fixtures, designed to illuminate the most discriminating office or home. A shallow contemporary opal acrylic diffuser softly and evenly distributes light at comfortable levels.

**LSMP Series**

40W (2820 Lumens)

**Specification Features**



**Construction**

Rugged construction, solid die formed, cold-rolled steel housing. All surfaces powder coated after fabrication. Frosted acrylic diffusers provides even consistent light while reducing glare. Lens design and materials provide uniform appearance without pixelation.

**Electrical**

Equipped standard with fixed output driver. Optional 0-10V continuous dimming driver that works with any standard 0-10V control/dimmer. Long-Life LED's 60,000 hours at L80 with projected life over 100,000 hours for reduced life cycle maintenance costs.

**Qualifications**

All luminaires are built to UL 1598 and 2108 standards, and bear appropriate ETL labels. Damp location labeling is standard. Emergency equipped fixtures labeled UL924. Adheres to LM70, LM80, and TM21 industry standards. ENERGY STAR® certified product (for 3000K and 4000K only) and Title 24 qualified. Dedicated 120V Models are FCC Title 47 CFR, Part 15, Class B for residential and commercial applications. California Title 24 Compliant, JA8 compliant, CEC Listed.

**Installation**

Suitable for surface mounting, suspension, or stem mounting, individually or in continuous rows.

**Warranty**

5-year limited warranty. See complete warranty for terms and exclusions. (Labor not included).

Rated Life 60,000 hours  
 Limited Warranty 5 years  
 Efficacy up to 88 LPW  
 Continuous Dimming



**Quick Ship**

LSMP-8-40-MV-940

**Ordering Information**

Example:LSMP-8-40-MV-940

LSMP	8	40	MVD	9	40
<b>Series</b> LSMP LED Surface Mounted Puff	<b>Size</b> 8- 8" Width	<b>Rated Wattage</b> 40- 40W (2820 Lumens)	<b>Driver Type</b> MV- 120-277V MVD- 120-277V; 0-10V Dimming <sup>1</sup>	<b>CRI</b> 9 90+CRI	<b>Color Temp</b> 40 4000K 50 5000K <sup>1</sup>

Specifications and Dimensions subject to change without notice.

Performance Summary

Input Voltage	120-277V
Input Frequency	50/60 Hz
Rated Wattage	See Performance Table
Delivered Lumens	See Performance Table
Efficacy	>88 lm/W
CRI	80+, R9 > 0
Available CCT <sup>1</sup>	4000K
Color Consistency <sup>2</sup>	5-step MacAdam Ellipse
Rated Life	60,000 hours
L70 <sup>3</sup>	> 72,000 hours or > 45,000
Power Factor	>0.99
THD	< 2.3%
Dimming	0-10V Continuous (10-100%)
Operating Temp.	-18°C to 40°C

Performance Data

Lens Type	Form Factor	Catalog No.	Rated Wattage (W)	Delivered Lumens	Efficacy (lm/W)
Frosted Acrylic	8"	LSMP-8-40-MV-940	40W	3,520	88

NOTES:

- <sup>1</sup> Made to order items. Minimum 90 day lead time. Minimum 500 order quantity.
- <sup>2</sup> Energy Star Listed
- <sup>3</sup>
- <sup>4</sup> Quick ship: 4000K. Other CCTs may require a lead time or be special order
- <sup>5</sup> Typical color consistency. May vary or be changed.
- <sup>6</sup> L70 hours calculated based on LED package manufacturer LM80 report and ISTMT report of LED in luminaire. Stated values are for select catalog numbers. Contact GlobaLux for detailed information.
- <sup>7</sup> Actual performance may differ as a result of end-user environment and application. All values are design or typical values, measured under laboratory conditions at 25 °C.




Specifications and Dimensions subject to change without notice.

Product Dimensions

---


LSMP-8



Photometric Data

LSMP-11- 40-940 Tested in accordance to IESNA LM-79

Polar Candela Curve



Zonal Lumen Summary

Zone	Lumens	% Lamp	% Luminaire
0-30	483	18.20%	18.30%
0-40	798.8	30.20%	30.20%
0-60	1,458.90	55.10%	55.10%
60-90	665.9	25.20%	25.20%
0-90	2,124.80	80.30%	80.30%

Coefficients of Utilization

Effective Floor Cavity Reflectance: 20%

RCC %:	80				70				50	
	70	50	30	0	70	50	30	0	50	30
RW %:	1.14	1.14	1.14	1.14	1.09	1.09	1.09	0.8	1	1
RCR: 0	1.02	0.96	0.91	0.87	0.97	0.92	0.87	0.63	0.84	0.8
1	0.92	0.83	0.75	0.69	0.87	0.79	0.72	0.51	0.72	0.67
2	0.83	0.72	0.63	0.56	0.79	0.69	0.61	0.43	0.63	0.57
3	0.76	0.63	0.54	0.47	0.72	0.61	0.52	0.36	0.56	0.49
4	0.7	0.56	0.47	0.4	0.66	0.54	0.45	0.31	0.5	0.42
5	0.64	0.51	0.41	0.35	0.61	0.48	0.4	0.28	0.45	0.37
6	0.59	0.46	0.37	0.3	0.56	0.44	0.36	0.24	0.41	0.33
7	0.55	0.41	0.33	0.27	0.52	0.4	0.32	0.22	0.37	0.3
8	0.51	0.38	0.3	0.24	0.49	0.37	0.29	0.2	0.34	0.27
9	0.48	0.35	0.27	0.22	0.46	0.34	0.26	0.18	0.31	0.25
10										



© 2019 GlobaLux Lighting, LLC. All rights reserved. For informational purposes only. Reproduction in whole or part is prohibited without prior written consent of the copyright owner. The information presented in this document does not form part of any quotation or contract, is believed to be accurate and reliable and may be changed without notice. No liability will be accepted by the publisher for any consequences of its use. GlobaLux Lighting reserves the rights make changes in specification at any time without notice.

GlobaLux Lighting LLC  
 www.globaluxlighting.com  
 2037 S. Vineyard Ave  
 Ontario, CA 91761  
 Ph: 909-591-7506