



Project	
Notes	
Type	Date
Cat. No.	

WCXS™ Series **Wet Location Exit & Combo Exit/Emergency**

APPLICATIONS

The WCXS (Wet Location Combo Exit/Emergency) series is engineered to perform in the most extreme environment. A fully gasketed polycarbonate lens and ABS housing enable the WCXS to be installed in locations that require Wet Location rated protection. Ideal for wet location areas requiring exit signs for AC only or battery back-up power that are subject to saturation with non-mechanically delivered water.



WCXS Series
WCXS-1-R
WCXS-1-G



Specification Features

Construction
5VA flame retardant, UV-stabilized polycarbonate gray finish. High-impact resistant, UV-stabilized polycarbonate clear lens. Knockouts provided for conduit feed applications. EZ snap-out Chevron directional indicators.

Qualifications
Meets UL924, NFPA 11 life safety Code, NEC, OSHA Local and State Codes. UL listed for wet locations (9° C - 40° C).

Warranty
5-year Limited Warranty on all electronics and housing. Battery pro rated for 5 years.

Electrical
Dual 120/277 voltage. Charge rate/power "ON" LED indicator light and push-to-test switch for mandated code compliance testing. 4.8V long-life, maintenance - free, rechargeable NiCad battery. Internal solid-state transfer switch automatically connects the internal battery to the LED lamp head for minimum 90-minute emergency illumination. Fully automatic solid-state, two-rate charger initiates battery charging to recharge a discharged battery in 24 hours.

Installation
Mounting hardware provided for back surface wall mount.

Limited Warranty 5-years

Quick Ship
Made to order only

Ordering Information

Example: WCXS-1-R

WCXS	1	G				
Series	Faces	Lettering	Battery			
WCXS- Wet Location Exit/Emergency Combo	1	R - Red G - Green	AC- AC Only EM- 90 minute battery			

Specifications and Dimensions subject to change without notice.

Performance Summary

Input Voltage	120V/277V
Input Frequency	50/60 Hz
Rated Wattage	6W
Operating Temp.	-18°C to 40°C
Rated Life	60,000 hours
L70	> 72,000 hours or > 45,000
Power Factor	> 0.9

Performance Data

Lens Type	Form Factor	Catalog No.	Rated Wattage (W)
None		WCXS-R	1.1
		WCXS-G	1.1

NOTES:

- ¹ Made to order items. Minimum 90 day lead time. Minimum 500 order quantity.
- ² Quick ship: 3000K. Other CCTs may require a lead time or be special order.
- ³ Actual performance may differ as a result of end-user environment and application. All values are design or typical values, measured under laboratory conditions at 25 °C.



Specifications and Dimensions subject to change without notice.

Product Dimensions

WCXS

