



**XT-RW-EM**  
**XT-GW-EM**  
**XT-RB-EM**  
**XT-GB-EM**

**DIMENSIONS:**



MODEL	VOLTAGE	NUMBER OF FACEPLATES	FACEPLATE	BATTERY	LETTERS COLOR
XT-RW-EM	Dual 120-277V	Single/Double	White	Ni-Cad	Red
XT-GW-EM	Dual 120-277V	Single/Double	White	Ni-Cad	Green
XT-RB-EM	Dual 120-277V	Single/Double	Black	Ni-Cad	Red
XT-GB-EM	Dual 120-277V	Single/Double	Black	Ni-Cad	Green

**LED EXIT SIGN**

**ELECTRICAL SPECIFICATIONS:**

- Voltage: Dual 120-277V
- Wattage: 3.2W(Red) & 3.8W(Green)

**HOUSING SPECIFICATIONS:**

- Universal canopy for side or top mounting on wall or ceiling
- Single or double faceplates
- Left or right arrow (Chevron)
- Low profile compact design, available in white or black housing
- Mounting accessories included
- Suitable for damp location (32°F to 122°F)

**CERTIFICATIONS: UL**



**TECHNICAL SPECIFICATIONS:**

- Solid state electronics and charger board
- Push-to-test switch
- Specification grade exit with Premium high-output ultra bright LEDs
- 4.8 V, Rechargeable Ni-Cad battery
- 90-minute EM-rated with push style test switch and red indicator light

**WARRANTY: 3 years**

- Meets UL924, NFPA life safety code, Local and State codes, NEC, OSHA

